



Yuasa Technisches Datenblatt

Yuasa YBX5020 - YBX5000 Silver High Performance SMF Batterien

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Leistung

Spannung 12V
Kapazität 20 Std (vorgegeben) 110Ah
Kaltstartstrom (A) EN1 950A

Abmessungen

Länge 393mm
Breite 175mm
Höhe 190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure 26.3kg



Gehäuseeigenschaften

Gehäusotyp L6 DIN
Batteriehälter B3
Ladezustandsanzeige ✓
Tragegriffe ✓
Entgasung ✓
Deckeltyp SMF doppelwandige Deckelkonstruktion


Technologie

Flammschutz ✓
Technologie Ca/Ca
Adskiller PE
VDA Überschlagentest ✓
Empfohlener Ladestrom 6A
Performance Marking W4-C2-V3-E1


Anschlusspol Typ

T1


Standard DIN Post



Zellenanordnung



Batteriehälter



Datenblatt erstellt am 13/06/2024 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX5020 - YBX5000 Silver High Performance SMF Batteries

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Performance

Voltage	12V
Capacity (20-hour)	110Ah
Cold Cranking Amps (EN1)	950A

Dimensions

Length	393mm
Width	175mm
Height	190mm



Weights & Measures

Mean Weight with Acid	26.3kg
-----------------------	--------

Container Features

Case Type	L6 DIN
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	6A
Performance Marking	W4-C2-V3-E1

Terminal Type

T1


Standard DIN Post




Positive Terminal

Negative Terminal

Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 13/06/2024 - E&OE